



1500RPM / 1800RPM Diesel Generator Ricardo Genset CE Certified

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-W22~W74
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 1800RPM Diesel Generator
- Engine Brand: Ricardo
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **1800RPM Diesel Generator,**
1500RPM Diesel Generator, Ricardo Genset

for more products please visit us on dellentpower.com

CE Ricardos Diesel Generator about 50kW.

. PRODUCT

Our Product Introduction

for more products please visit us on dellentpower.com

50 Hz				60 Hz		TECHNICAL DATA				RICARDO WATER-COOLED Series Diesel Generator Sets									
Genset Performance						Engine Performance						Dimension(L×W×H)							
Genset Model	Prime Power		Standby Power		Engine model	Speed	Prime power	Fuel Cons. (100% Load)	Cylinder Bore×Stroke	Displacement	Open Type		Silent Type						
	kW	kVA	kW	kVA							mm	mm							
DE-W22	16	20	18	22	4YT23-20D	1500	20	≤ 240	4	88×95	2.31	130×78×96	220×93×123						
DE-W27	20	25	22	27	N4100DS-30	1500	30	≤ 225	4	100×115	3.61	130×78×96	220×93×123						
DE-W33	24	30	26	33	N4100DS-30	1500	30	≤ 225	4	100×115	3.61	130×78×96	220×93×123						
DE-W41	30	38	33	41	N4105DS-38	1500	38	≤ 220	4	105×120	4.15	130×78×96	220×93×123						
DE-W55	40	50	44	55	N4105ZDS	1500	56	≤ 210	4	105×120	4.15	153×78×115	230×93×123						
DE-W66	48	60	53	66	N4105ZDS	1500	56	≤ 210	4	105×120	4.15	159×78×115	239×93×123						
DE-W74	54	68	59	74	N4105ZLDS	1500	66	≤ 210	4	105×120	4.15	159×85×121	239×98×128						
DE-W96	70	88	77	96	R6105ZDS	1500	84	≤ 220	6	105×125	6.49	186×90×121	285×108×160						
DE-W96	70	88	77	96	4RT55-88D	1500	88	≤ 205	4	110×140	5.32	178×85×121	260×108×150						
DE-W110	80	100	88	110	R6105ZLDS	1500	100	≤ 218	6	105×125	6.49	186×90×121	285×108×160						
DE-W110	80	100	88	110	4RT55-88D	1500	88	≤ 205	4	110×140	5.32	186×90×121	280×105×150						
DE-W132	96	120	106	132	4RT55-110D	1500	110	≤ 205	4	110×140	5.32	186×90×121	280×105×150						
DE-W138	100	125	110	138	R6105AZLDS	1500	121	≤ 218	6	105×130	6.75	235×103×160	300×110×150						
DE-W165	120	150	132	165	R6105BZLDS	1500	132	≤ 218	6	105×135	7.01	235×103×160	315×120×162						
DE-W165	120	150	132	165	6RT80-132D	1500	132	≤ 205	6	110×140	7.98	235×103×160	315×120×162						
DE-W220	160	200	176	220	6RT80-176DE	1500	176	≤ 205	6	110×140	7.98	273×105×172	340×130×185						
DE-W275	200	250	220	275	WT10B-231DE	1500	231	≤ 205	6	126×130	10.09	279×105×172	380×130×200						
DE-W344	250	313	275	344	WT13B-308DE	1500	308	≤ 205	6	131×155	12.53	279×105×172	400×135×210						
DE-W413	300	375	330	413	WT13B-330DE	1500	330	≤ 205	6	131×155	12.53	279×105×172	400×135×210						
DE-W18	13	16	14	18	4YT23-20D	1800	22	≤ 240	4	88×95	2.31	130×78×96	220×93×123						
DE-W25	16	20	18	25	N4100DS-30	1800	33	≤ 225	4	100×115	3.61	130×78×96	220×93×123						
DE-W31	22	28	24	31	N4100DS-30	1800	33	≤ 225	4	100×115	3.61	130×78×96	220×93×123						
DE-W37	27	33	30	37	N4100DS-30	1800	33	≤ 220	4	100×115	3.61	130×78×96	220×93×123						
DE-W47	34	43	37	47	N4105DS-38	1800	41.8	≤ 210	4	105×120	4.15	130×78×96	230×93×123						
DE-W55	40	50	44	55	N4100ZDS-42	1800	46.2	≤ 210	4	105×120	4.15	130×78×96	239×93×123						
DE-W69	50	63	55	69	N4105ZDS	1800	61.6	≤ 210	4	105×120	4.15	153×78×115	239×98×128						
DE-W83	60	75	66	83	N4105ZLDS	1800	72.6	≤ 220	4	105×120	4.15	159×78×115	285×108×160						
DE-W91	66	83	73	91	4RT55-88D	1800	96.8	≤ 205	4	110×140	5.32	159×85×121	260×108×150						
DE-W106	77	96	85	106	R6105ZDS	1800	92.4	≤ 218	6	105×125	6.49	186×90×121	285×108×160						
DE-W110	80	100	88	110	4RT55-88D	1800	96.8	≤ 205	4	110×140	5.32	178×85×121	280×105×150						
DE-W124	90	113	99	124	R6105ZLDS	1800	110	≤ 205	6	105×125	6.49	186×90×121	290×105×150						
DE-W124	90	113	99	124	4RT55-110D	1800	121	≤ 218	4	110×140	5.32	186×90×121	280×105×150						
DE-W138	100	125	110	138	4RT55-110D	1800	121	≤ 218	4	110×140	5.32	186×90×121	280×105×150						
DE-W151	110	138	121	151	R6105AZLDS	1800	133.1	≤ 205	6	105×130	6.75	235×103×160	315×120×162						
DE-W179	130	163	143	179	R6105BZLDS	1800	145.2	≤ 205	6	105×135	7.01	235×103×160	315×120×162						
DE-W179	130	163	143	179	6RT80-132D	1800	145.2	≤ 205	6	110×140	7.98	235×103×160	305×130×185						
DE-W220	160	200	176	220	6RT80-176DE	1800	193.6	≤ 205	6	110×140	7.98	273×105×172	340×130×185						

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



- 1: The diesel generator should be placed in a well ventilated area to ensure heat dissipation;
- 2: Diesel generators should regularly inspect and replace vulnerable parts such as engine oil and air filter elements to ensure their normal operation;
- 3: Diesel generators should be avoided from being used in high-temperature environments to avoid affecting the performance of the diesel engine;
- 4: Diesel generators should be avoided in environments with high levels of dust to avoid affecting heat dissipation.



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDECITY,FUJIAN.CHINA